



SAFETY DATA SHEET

LGFP 2

Last changed: 13/12/2010

Replaces date: 01/11/2007

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

TRADE NAME LGFP 2
APPLICATION AREA Fat.

NATIONAL MANUFACTURER/IMPORTER

Enterprise SKF Maintenance Products
Address Postbus 1008
Postal code NL-3430 BA Nieuwegein
Country The Netherlands
Telephone +31 30 6307200
Fax +31 30 6307205

CONTACT PERSONS

Name	E-mail	Telephone	Country
David Sébastien	sebastien.david@skf.com	+ 31 30 6307200	The Netherlands

Emergency Phone	Type of assistance	Opening Hours
+ 47 22 59 13 00	Giftinformasjonen	24 timer

2. HAZARDS IDENTIFICATION

HEALTH

May be irritating to eyes.
Prolonged or frequently recurrent contact will degrease the skin and may cause skin irritation.

FIRE AND EXPLOSION

Not flammable, but combustible.

ENVIRONMENT

Oil products may cause ground and water pollutants.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient name	Reg.No	EC No.	CAS No.	Conc. (wt%)	Classification
white mineral oil (petroleum)		232-455-8	8042-47-5	60 - 100 %	No classification required
Explanation of symbols: T+=highly toxic, T=toxic, C=corrosive, Xn=harmful, Xi=irritant E=Explosive, O=Oxidising, F+=Extremely flammable, F=Highly flammable, N=Dangerous for the environment, Cancer=Carcinogenic, Mut=Mutagenic, Rep=Toxic for reproduction, Conc.=Concentration					

4. FIRST AID MEASURES

INHALATION

Provide rest, warmth and fresh air. Seek medical advice if symptoms develop.

SKIN CONTACT

Wash with soap and water and apply skin cream, if necessary. Remove contaminated clothing. Seek medical advice if irritation persists.

EYE CONTACT

Immediately flush eyes with plenty of water while holding eye lids open. Remove any contact lenses and continue rinsing with water for at least 15 minutes (keep the eyelids open). Seek medical advice if irritation persists.

INGESTION

DO NOT INDUCE VOMITING! If vomiting occurs, keep head low so that stomach contents do not enter lungs. Thoroughly rinse the mouth with water. Drink a few glasses of water or milk. Seek medical advice.

5. FIRE-FIGHTING MEASURES



SAFETY DATA SHEET

LGFP 2

Last changed: 13/12/2010

Replaces date: 01/11/2007

EXTINGUISHING MEDIA

Extinguishing agent: carbon dioxide, powder, foam, water spray or water mist. Cover with dry sand.

IMPROPER EXTINGUISHING MEDIA

Do not use a direct water stream which may spread the fire.

EXTINGUISHING METHODS

Remove containers from fire area if this can be done without risk. Use water to cool exposed containers. If possible, fight the fire from a protected location.

FIRE AND EXPLOSION HAZARDS

Not flammable, but combustible. Carbon monoxide and hydrocarbons are released in a fire situation.

PROTECTIVE EQUIPMENT FOR FIRE FIGHTERS

General: Evacuate all personnel, use protective equipment for fire fighting. Use a portable breathing apparatus when the product is involved in a fire.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Provide good ventilation. Avoid contact with the skin, eyes and airways. Wear necessary protective equipment. Keep the emission away from sources of ignition.

SAFETY ACTIONS TO PROTECT EXTERNAL ENVIRONMENT

Must not be released into the sewage system, drinking water supply or ground.

METHODS FOR CLEANING UP

Dry, scrape or absorb the product with inert material and place it in a refuse container. Collect and dispose of materials in closed and labelled containers at an approved disposal or waste collection facility. Clean with soap and water or detergent. Flush clean with plenty of water. Be aware of the risk of slippery surfaces.

7. HANDLING AND STORAGE

HANDLING ADVICE

Provide good ventilation. Avoid contact with the skin and eyes. Wear necessary protective equipment. Keep away from sources of ignition.

STORAGE

Keep in a dry, cool and well-ventilated area. Keep in original container. Keep containers tightly closed. Avoid contact with oxidising substances.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE CONTROL

Provide good ventilation. Wash the skin at the end of each work shift and before eating, smoking and using restroom facilities. Eye wash facilities and safety shower must be available when handling this product.

RESPIRATORY PROTECTION

Respiratory protective equipment is usually not necessary. In case of insufficient ventilation, wear respiratory protective equipment with A/P2 filter.

EYE PROTECTION

Wear approved safety goggles if there is a risk of eye splash.

HAND PROTECTION

Protective gloves (nitrile rubber, Viton®).



SAFETY DATA SHEET

LGFP 2

Last changed: 13/12/2010

Replaces date: 01/11/2007

PROTECTIVE CLOTHING

Wear suitable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE Paste.
COLOUR Transparent.
ODOUR Characteristic.
WATER SOLUBILITY Insoluble in water.

Physical and chemical parameters

Parameter	Value/unit	Method/reference	Observation
Flash point	> 200.00 °C		
Density	0.92 - 0.96 g/cm ³		
Viscosity	120.00 - 140.00 mm ² /s	DIN 51562/1 / 40 °C	
Dropping point	> 250 °C / DIN ISO 2176		

10. STABILITY AND REACTIVITY

STABILITY

Stable under recommended storage and handling conditions.

CONDITIONS TO AVOID

Avoid heat, sparks and naked flames.

MATERIALS TO AVOID

Avoid contact with oxidising substances.

11. TOXICOLOGICAL INFORMATION

INHALATION

On warming/heating, the vapours emitted may cause irritation to the respiratory organs. May cause coughing and breathing difficulties.

SKIN CONTACT

Prolonged or frequently recurrent contact will degrease the skin and may cause skin irritation. May cause redness.

EYE CONTACT

May cause moderate irritation/smartering.

INGESTION

May cause irritation of the mucous membranes, nausea and vomiting.

12. ECOLOGICAL INFORMATION

MOBILITY

Insoluble in water.

DEGRADABILITY

Slowly biodegradable.

ACCUMULATION

No information available

OTHER EFFECTS

Oil products may cause ground and water pollutants.



SAFETY DATA SHEET

LGFP 2

Last changed: 13/12/2010

Replaces date: 01/11/2007

CONCLUSION

Slowly biodegradable.

Must not be released into the sewage system, drinking water supply or ground.

OTHER INFORMATION

German water pollution classification (WGK): 1 Water pollutant.

13. DISPOSAL CONSIDERATIONS

GENERAL REGULATIONS

Treat as hazardous waste. Collect and dispose of materials in closed and labelled containers at an approved disposal or waste collection facility. Empty packages must be handled in an environmentally safe manner in accordance with applicable laws and regulations.

CATEGORY OF WASTE

The EWC code is a suggestion only; the end user will select a suitable EWC code. 12 01 12* spent waxes and fats

Waste product number: 7021 Oily and greasy waste.

14. TRANSPORT INFORMATION

Classified as Dangerous Goods: **No**

15. REGULATORY INFORMATION

EC-Label: No

COMPOSITION

white mineral oil (petroleum) (60 - 100 %)

S-PHRASES

S24/25 Avoid contact with skin and eyes.

S37 Wear suitable gloves.

REFERENCES

Directive 1999/45/EC.

Annex VI to Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Dangerous Substances.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

European Waste Catalogue.

Occupational exposure limits (EH40/2005).

Transport of dangerous goods: ADR, RID, IMDG and IATA.

16. OTHER INFORMATION

ISSUED: 18/04/2006