



# SAFETY DATA SHEET

## LGMT 3

Last changed: 07/03/2011

Replaces date: 01/05/2008

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**TRADE NAME** LGMT 3  
**APPLICATION AREA** Fat.

#### NATIONAL MANUFACTURER/IMPORTER

**Enterprise** SKF Maintenance Products  
**Address** Postbus 1008  
**Postal code** NL-3430 BA Nieuwegein  
**Country** The Netherlands  
**Telephone** +31 30 6307200  
**Fax** +31 30 6307205

#### CONTACT PERSONS

Name	E-mail	Telephone	Country
David Sébastien	sebastien.david@skf.com	+ 31 30 6307200	The Netherlands

### 2. HAZARDS IDENTIFICATION

#### HEALTH

May be irritating to eyes.

Prolonged or frequently recurrent contact will degrease the skin and may cause skin irritation.

#### FIRE AND EXPLOSION

Not flammable, but combustible.

#### ENVIRONMENT

Oil products may cause ground and water pollutants.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient name	Reg.No	EC No.	CAS No.	Conc. (wt%)	Classification
baseoil-unspecified		-	-	60 - 100 %	No classification required
zinc naphthenate		234-409-2	12001-85-3	1,7 %	Xi,N,R36/38 - R51/53

Explanation of symbols: T+=highly toxic, T=toxic, C=corrosive, Xn=harmful, Xi=irritant E=Explosive, O=Oxidising, F+=Extremely flammable, F=Highly flammable, N=Dangerous for the environment, Cancer=Carcinogenic, Mut=Mutagenic, Rep=Toxic for reproduction, Conc.=Concentration

#### INGREDIENT COMMENTS

The complete text of the R-phrases mentioned in section 3 is stated in section 16.

### 4. FIRST AID MEASURES

#### INHALATION

Remove victim immediately from source of exposure. Provide rest, warmth and fresh air. Seek medical advice if symptoms develop.

#### SKIN CONTACT

Immediately flush contaminated skin with soap or mild detergent and water. Immediately remove soaked clothing and flush the skin with water. Use appropriate hand lotion to prevent degreasing and cracking of skin. Seek medical advice if irritation persists.

#### EYE CONTACT

Immediately flush eyes with plenty of water while holding eye lids open. Remove any contact lenses and continue rinsing with water for at least 15 minutes (keep the eyelids open). Seek medical advice if irritation persists.

#### INGESTION

DO NOT INDUCE VOMITING! If vomiting occurs, keep head low so that stomach contents do not enter lungs. Thoroughly rinse the mouth with water. Drink a few glasses of water or milk. Seek medical advice.



# SAFETY DATA SHEET

LGMT 3

Last changed: 07/03/2011

Replaces date: 01/05/2008

## 5. FIRE-FIGHTING MEASURES

### EXTINGUISHING MEDIA

Extinguishing agent: carbon dioxide, powder, alcohol-resistant foam, water spray or water mist.

### IMPROPER EXTINGUISHING MEDIA

Do not use a direct water stream which may spread the fire.

### EXTINGUISHING METHODS

Use water to cool exposed containers. Remove containers from fire area if this can be done without risk. If possible, fight the fire from a protected location.

### FIRE AND EXPLOSION HAZARDS

Not flammable, but combustible. Carbon monoxide and hydrocarbons are released in a fire situation.

### PROTECTIVE EQUIPMENT FOR FIRE FIGHTERS

General: Evacuate all personnel, use protective equipment for fire fighting. Use a portable breathing apparatus when the product is involved in a fire.

## 6. ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

Provide good ventilation. Avoid contact with the skin, eyes and airways. Wear necessary protective equipment. Keep the emission away from sources of ignition.

### SAFETY ACTIONS TO PROTECT EXTERNAL ENVIRONMENT

Prevent discharge to the sewage system, waterways or ground.

### METHODS FOR CLEANING UP

Stop leak if this can be done without risk. Dry, scrape or absorb the product with inert material and place it in a refuse container. Collect and dispose of materials in closed and labelled containers at an approved disposal or waste collection facility. Clean with soap and water or detergent. Flush clean with plenty of water. Be aware of the risk of slippery surfaces.

## 7. HANDLING AND STORAGE

### HANDLING ADVICE

Provide good ventilation. Wear necessary protective equipment. Keep away from sources of ignition. Take precautionary measures against static discharges.

### STORAGE

Stored in a well-ventilated area away from sources of ignition. Store at room temperature. Keep in original container. Avoid contact with oxidising substances, strong acids and strong bases.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### EXPOSURE CONTROL

Provide good ventilation. Wash the skin at the end of each work shift and before eating, smoking and using restroom facilities. Eye wash facilities and safety shower must be available when handling this product.

### RESPIRATORY PROTECTION

Respiratory protective equipment is usually not necessary. In case of insufficient ventilation, wear respiratory protective equipment with A/P2 filter.

### EYE PROTECTION

Wear approved safety goggles if there is a risk of eye splash.



# SAFETY DATA SHEET

## LGMT 3

Last changed: 07/03/2011

Replaces date: 01/05/2008

### HAND PROTECTION

Protective gloves (butyl rubber, nitrile rubber, Viton, 4H).

### PROTECTIVE CLOTHING

Wear suitable protective clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE** Paste.

**COLOUR** Amber.

**ODOUR** Mild.

**WATER SOLUBILITY** Insoluble in water.

### Physical and chemical parameters

Parameter	Value/unit	Method/reference	Observation
Flash point	> 220.00 °C	ASTM D 93 / Base Oil	
Auto-ignition temp.	> 350.00 °C	ASTM D 659	
Decomposition temp.	> 350.00 °C		
Density	0.95 g/cm <sup>3</sup>		
Drop point	> 180 °C ASTM D 566		
N.L.G.I Penetration	3 ASTM D 217		

## 10. STABILITY AND REACTIVITY

### STABILITY

Stable under recommended storage and handling conditions.

### CONDITIONS TO AVOID

Keep away from sources of ignition. Avoid temperatures above 350 °C. Static electricity and formation or sparks must be prevented.

### MATERIALS TO AVOID

Avoid contact with oxidising substances, strong acids and strong bases.

## 11. TOXICOLOGICAL INFORMATION

### ACUTE TOXIC TEST RESULTS

LGMT 3				
Route of exposure	Exposure time	Value/unit	Species	Source
LD50 (Oral)		> 2000.00 mg/kg	Rat	Producer

### INHALATION

On warming/heating, the vapours emitted may cause irritation to the respiratory organs. May cause coughing and breathing difficulties.

### SKIN CONTACT

Prolonged or frequently recurrent contact will degrease the skin and may cause skin irritation.

### EYE CONTACT

May cause moderate irritation/smartering.

### INGESTION

May cause irritation of the mucous membranes, nausea and vomiting.

## 12. ECOLOGICAL INFORMATION



# SAFETY DATA SHEET

## LGMT 3

Last changed: 07/03/2011

Replaces date: 01/05/2008

### AQUATIC ECOTOXICITY

#### LGMT 3

Test	Exposure time	Value/unit	Species	Source
LC50 (Acute fish)		> 100.00 mg/l		Producer

### MOBILITY

Insoluble in water.

### DEGRADABILITY

Difficultly biodegradable.

### OTHER EFFECTS

Oil products may cause ground and water pollutants.

### CONCLUSION

Difficultly biodegradable.

Oil products may cause ground and water pollutants.

Prevent discharge to the sewage system, waterways or lakes.

### OTHER INFORMATION

German water pollution classification (WGK):2

---

## 13. DISPOSAL CONSIDERATIONS

---

### GENERAL REGULATIONS

Treat as hazardous waste. Collect and dispose of materials in closed and labelled containers at an approved disposal or waste collection facility. Empty packages must be handled in an environmentally safe manner in accordance with applicable laws and regulations.

### CATEGORY OF WASTE

The EWC code is a suggestion only; the end user will select a suitable EWC code. 13 02 08\* other engine, gear and lubricating oils

Waste product number: 7021 Oily and greasy waste.

---

## 14. TRANSPORT INFORMATION

---

**Classified as Dangerous Goods:** No

### OTHER INFORMATION

Not classified as dangerous goods.

---

## 15. REGULATORY INFORMATION

---

**EC-Label:** No

### COMPOSITION

baseoil-unspecified (60 - 100 %), zinc naphtenate (1,7 %)

### S-PHRASES

S24/25 Avoid contact with skin and eyes.

S37/39 Wear suitable gloves and eye/face protection.



## SAFETY DATA SHEET

### LGMT 3

Last changed: 07/03/2011

Replaces date: 01/05/2008

#### REFERENCES

Directive 1999/45/EC.

Annex VI to Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Dangerous Substances.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

European Waste Catalogue.

Occupational exposure limits (EH40/2005 ).

Transport of dangerous goods: ADR, RID, IMDG and IATA.

#### 16. OTHER INFORMATION

##### LIST OF RELEVANT R-PHRASES

R36/38 Irritating to eyes and skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**ISSUED:** 24/02/2006